

DECLARATION OF PERFORMANCE

TWEHA TAPE; DoP No. TWEHA-TAPE-4.0 / 07-09-2026

1. Unique identification code of the product-type:

TWEHA Tape

2. Type, batch or serial number or any other element allowing identification of the construction product:

The batch and/or production identification is indicated on the product label and/or packaging.

3. Intended use of the construction product:

Double-sided self-adhesive foam tape intended for use as a non-structural accessory within TWEHA bonding systems for the installation of rainscreen and ventilated façade cladding.

TWEHA Tape provides the initial fixation of the façade panel during curing of the structural adhesive and ensures the minimum required adhesive layer thickness of 3 mm.

TWEHA Tape is not intended to transfer permanent structural loads. The structural connection between the façade panel and supporting structure is provided exclusively by the applicable TWEHA adhesive.

4. Name, registered trade name or registered trademark and contact address of the manufacturer:

TcB

Lepelstraat 1, bus 02.01 - B-3920 Lommel – Belgium

Chamber of Commerce: 56565860 - RSIN: 852189187

T: +31 88 600 36 00 - E: info@tweha.com - W: www.tweha.com

5. Authorized representative:

Inapplicable.

6. System of assessment and verification of constancy of performance (AVCP):

Inapplicable. No European harmonized product standard (hEN) applicable to TWEHA Tape as a standalone spacer/fixing tape has been identified and no European Technical Assessment (ETA) has been issued for TWEHA Tape as a standalone product.

TWEHA Tape is supplied and used as a non-structural accessory to the TWEHA bonding system.

7. Harmonized standard / European Assessment Document / European Technical Assessment:

Inapplicable.

8. Product function and limitations:

TWEHA Tape is intended to:

provide immediate temporary fixation of the façade panel;

maintain the required distance between façade panel and supporting structure;

ensure a minimum final adhesive bead thickness of 3 mm;

accommodate minor surface irregularities;

prevent premature compression of the structural adhesive bead.

TWEHA Tape shall not be included in structural calculations and shall not be considered as contributing to the permanent load-bearing capacity of the bonded façade connection.

9. Declared product performance

Characteristic	Declared performance
Product type	Double-sided self-adhesive foam tape
Standard dimension	12 × 3 mm
Roll length	25 m
Nominal spacer thickness	3 mm
Elongation	175%
Force to compress 50%	0.15 MPa
Temperature range	–40°C to +60°C
Ageing resistance	Good
Moisture resistance	Very Good
Function in TWEHA bonding system	Initial fixation and dimensional spacer
Permanent structural load transfer	Not applicable
Reaction to fire	NPD
Dangerous substances	See applicable REACH/SDS information

De technische waarden hierboven volgen het bestaande Technical Data Sheet van TWEHA Tape.

10. Declaration


The product identified above is manufactured and supplied in conformity with the product characteristics declared in this document.

TWEHA Tape is an accessory to the TWEHA bonding system and is not a structural adhesive or permanent load-bearing fixing component. Its function is limited to initial fixation during installation and maintaining the prescribed adhesive layer thickness.

This declaration is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Lommel, September 7, 2026



M.J.P. van Leeuwen, General Director

Annex to the declaration of performance in accordance with Article 6(5) of Building Regulation and the REACH Regulation No. 1907/2006, Article 31 or 33

- 1 (31) Material safety data Sheet (MSDS): available on www.tweha.com
- 2 (33) information on substances of very high concern (SCHC): inapplicable